VKSM-104 (without audio) VKSMA-104 (with audio)



4K2K HDMI 4-Port Splitter

Specifications

Model		VKSM-104	VKSMA-104
Connectors	Input	HDMI Female x 1	HDMI Female x 1, 3.5mm Audio Jack x 1
	Output	HDMI Female x 4	HDMI Female x 4
			3.5mm Audio Jack x 4
Video Resolution (Max.)		4K2K (3840 x 2160) Full HD 1080p (1920 x 1080)	
Support 3D Mode		Mandatary 3D (1080p / 720p)	
LED Indicators	Power/Input (Status)	Multiple color x 1	
	Video output	Single color x 4	
HDMI Supports TMDS Clock Rate (Max.)		300 MHz	
Rack Mountable (optional)		Yes	
EDID Copy Button		1	
Enclosure		Metal	
Power Consumption (Max.)		Max. 130mA @ 12V	
Dimensions H x W x D (mm)		42 x 218 x 130	
Weight (g)		950~990	

Video Splitter Aport / / / / / Powerloput HDCP Ready

Features

- Provide an easy and affordable way to duplicate one video input to multiple HDMI outputs
- Automatic power-saving when losing signal input
- Cascaded operation for increased signal outputs
- Crisp clear video images
- Mandatory 3D-video, HDCP compliant and Bluray ready for high definition display
- Support HDMI display resolutions up to UHD (3840 x 2160), Full HD 1080p (1920 x 1080), WUXGA (1920 x 1200), & UXGA (1600 x 1200)
- 3.5mm independent audio channel outputs for speakers (VKSMA-104 only)
- · LED indicators for monitoring signal activity
- Accurate and reliable reproduction of digital video signals without attenuation and distortion
- Can be installed in seconds
- Unique EDID Copy function for high definition display
- Rack mountable

▶ Connection Pattern

