

Wall-Plate HDMIx2 / VGA+Audio Transmitter over HDBaseT

Specifications

Model	Transmitter	
	EVBMV-A1371WL	EVBMV-A1391WL
Input	HDMI x 2 VGA + Analog Stereo x 1	
Output	HDMI x 1	
Connection	RJ-45 x 1	
LED Indicator (Power / Status)	Source x 3 Remote x 1, Local x 1	
Push Button	SELECT x 1, ALT x 1 Copy x 1 (under the cover)	
Serial Configuration	RJ-12 x 1 (Control)	
Mode Configuration	Pri-VGA/DP / Pri-HDMI / Auto / Manual	
Video Resolution (Max.)	UHD (3840 x 2160) for HDMI Full HD (1920 x 1080) for VGA	
Extension Distance*	HDMI 70M @ Full HD (1920 x 1080) 35M @ UHD (3840 x 2160)	HDMI 100M @ Full HD (1920 x 1080) 70M @ UHD (3840 x 2160)
	VGA 70M @ Full HD (1920 x 1080)	VGA 100M @ Full HD (1920 x 1080)
Enclosure	Metal	
Power Supply	DC 12V	

*Above video resolution and extension distance are based on a single CATx 24AWG solid cable without cascade. STP cabling is recommended for environments with high EMI or RFI. For the best performance results, using stranded cabling or other thinner cables, and coiling of excess cable lengths should be avoided.

Features

- Transmit HDMI / VGA with analog audio signal up to 70 / 100 meters
- Uses HDBaseT™ technology
- Auto EQ (Sharpness) adjustment for optimal signal clarity
- Screen Shift Mode provides user to adjust image's shifting
- Use Resolution Alternation Mode when catching multiple similar video timing
- Input source sequence selectable
- Auto-sensing function enables the system to automatically select the latest video source
- Support resolutions up to UHD (3840 x 2160) and Full HD (1920 x 1080) and compatible with most of the popular screen resolution
- HDCP compliant, 3D-video and Blu-ray ready over single CATx cable
- Plug-and-Play system without any drivers or software installation



Related Products

Type	100M	Function
Rx	EVBM-107R EVBM-110R	CATx HDMI Receiver (Max. 4K2K)
	EVBM-K107R EVBM-K110R	CATx HDMI Receiver with Scaling (Max. Full HD 1080p)

Connection Pattern

