

EXXAS-2022



Two-Access CAT.x Dual-View 200M KVM Extender with Audio & Serial & IR EXT.

► Specifications

Model		EXXAS-2022		
MAX. Resolution		1920x1200 / 1600x1200		
Extension Distance		200M		
Link Port		RJ45 x 1 (Video) RJ45 x 1 (Video + Control)		
Computer Unit (EXXAS-021P)	Console Side	Keyboard/ Mouse	USB HID-A x 2	
		Display	HDB15-Female x 2 (Blue)	
		Audio	Speaker x 1 & MIC x 1	
		Serial	DB9-Male x 1 (DTE)	
	Computer Side	Connection	HDB15 Female x 1 (Grey : VGA+Control) HDB15-Female x 1 (Blue : VGA only)	
		Audio	Speaker x 1 & MIC x 1	
		Serial	DB9-Female x 1 (DCE)	
	IR Remote Control		3.5mm x 1 (to IR Transmitter)	
	Mask Hotkey Selection		Slide Switch x 1	
	Power Supply		DC9~12V (External AC100~240V Power Adpter Included)	
Operating Temperature		5~50°C		
Console Unit (EXXAS-202S)	Console Side	Keyboard/ Mouse	USB HID-A x 2	
		Display	HDB15-Female x 2 (Blue)	
		Audio	Speaker x 1 & MIC x 1	
		Serial	DB9-Male x 1 (DTE)	
	Computer Side	Connection	HDB15 Female x 1 (Grey : VGA+Control) HDB15-Female x 1 (Blue : VGA only)	
		Audio	Speaker x 1 & MIC x 1	
		Serial	DB9-Female x 1 (DCE)	
	IR Remote Control		3.5mm x 1 (to IR Receiver)	
	Mask Hotkey Selection		Slide Switch x 1	
	Power Supply		DC9~12V (External AC100~240V Power Adpter Included)	
Operating Temperature		5~50°C		
Serial Baud Rate (Max.)		115200bps		
Front Panel LEDs		Local / Remote Status x 2 Serial Status x 2		
Push Button		Control Status Selection		
Hotkey Control		Yes		
Weight (g)		630~660 (each unit)		
Dimensions H x W x D (mm)		39 x 140 x 100		

- Applicable for one console to manage two computers locally and remotely
- Support the dual view function which can split your window (browser/ work area...) into two
- Remotely locate the keyboard, mouse and monitor up to **200 meters** away from a computer with the maximum resolution of 1920 x 1200 (WUXGA), **2048 x 1152** (QWXGA) and compatible with most of the popular screen resolution
- Independently adjust video quality, inclusive of Equalizer (sharpness), Gain (brightness) and RGB skew, among two CAT5 cables
- Synchronize the video resolution between the attached computers via hotkeys
- EDID Configuration function makes the best resolution to your application
- Dedicated Mask Hotkey function enables the direct control in cascading
- Simple LED indication makes operation user friendly
- IR extension available
- Support audio (Speaker & MIC) extension function
- Support serial interface for instant data transfer
- Support USB (HID) console
- Support the surge protection

Also Available:
Dual-Head VGA KVM Extender
Dual-Head VGA + Audio KVM Extender
Dual-Head VGA + Serial KVM Extender

► Connection Pattern

