

PAAG-114



4-Port DisplayPort KVM Switch w/ Audio & Hotkey Control

► Specifications

		PAAG-114
Console Port		1
Computer Port		4
Front Panel Push Button		4
Automatic Scan Interval		3, 8, 15, 30 Seconds
Cable Length (Max)		3M (10ft) for USB
Computer ON-LINE LED		4
Computer Selected LED		4
Hot Plug-and-Play		Yes
Console Interface	USB Port	4 (KB+MS+Extra USB 2.0)
	KB	USB
	MS	USB
	Monitor	DisplayPort
	Audio Jack (Speaker+Mic)	1 Set
Computer Interface	KB	USB
	MS	
	Monitor	DisplayPort
	Audio Jack (Speaker+Mic)	1 Set
Hotkey		Yes
OSD		No
Resolution		2560 x 1600
DDC2B		Yes
H x W x D (mm)		44 x 220 x 130

► Features

- Support USB console
- 4 computers share 4 different USB peripherals (KB + MS + USB 2.0 Devices)
- Support Audio (Speaker + Mic)
- Supports hot plug and un-plug detection and link status-failure detection
- Front panel push buttons for easy computer selection
- Buzzer sound for computer switching confirmation
- Hotkey functions allow easily computer access
- Supports existing VESA and Consumer Electronics Association (CEA) standards
- Screw-free design ,streamlined form factor for new all digital desktop monitors
- Complete interoperability

► Connection Pattern

