IDM-Q104D/ IDM-Q108D/ IDM-Q116D



4/8 / 16-Port DVI KVM Module w / Built-In AC Power

Rextron

Specifications

| | | IDM-Q104D IDM-Q108D | IDM-Q116D |
|--|------------------------------|---|----------------|
| Number of Console Ports | | | |
| Number of Computer Ports | | 4/ 8 | 16 |
| Applicable to computer | | USB PC, USB-Sun, USB-Mac | |
| On-Screen Display (OSD) | | Yes | |
| Plug-n-Play | | Yes | |
| Hotkey Control | | Yes | |
| Computer Name Entry | | 14-Character | |
| Auto-Scan Interval | | 3, 8,15, 30 Seconds | |
| Programmable Scan Pattern | | Yes | |
| Security Control | | 4-Character Password Per CPU | |
| Cable Type | | DVI 2-to-2 Cable | |
| Video Resolution (Max) | | 2048 x 1152, WUXGA (1920 x 1200) 1920 x 1080 (Full HD) | |
| Computer Connectors | | DVI-D Female | DVI-D Female |
| | | USB Interface | USB Interface |
| Console Connectors | Keyboard Mouse Monitor | USB mouse x 1 USB keyboard x 1 (also for keyboard with mouse) HDB15 female x 1 | |
| Size | | 1U | 1.5U |
| Power Consumption (Max.) (Built-in Power AC 100-240V) | | 8 W | 10 W |
| Dimensions H x W x D (mm) | | 40 x 404 x 114 | 59 x 404 x 155 |

Features

- Supports for USB keyboard and USB mouse
- DVI Interface w / Built-In AC Power
- Supports Sun servers, HP servers and Mac
- 1U-height form factor saves rack spaces
- Unique cables for secured connection
- Auto-scan function automatically selects computer sequentially
- Assigns computers with individual names
- Identifies and selects computers by chosen names
- Programmable scan filters unused computers.
- Password security locks computer from unauthorized access
- Complete control with easy-to-use OSD interface
- Hotkey functions allow easily computer access
- Operating system independent and transparent to all applications
- Plug-n-play system configuration
- DDC2B compatible
- Compatible with most of the popular screen resolution to XGA, SXGA, WSXGAFull HD, WUXGA system

Connection Pattern

