

IUM-2108D/ IUM-2116D

8 / 16-Port Two Access USB+PS/2 KVM Module w/ OSD




Specifications

		Slim USB + PS/2	
		IUM-2108D	IUM-2116D
Number of Console Ports		2	
Number of Computer Ports		8	16
Max Cascade Computers		64	136
Cable Type		1-to-3 (PS/2) or 1-to-2 (USB) Cable	
Applicable to Computer		PC, Sun, Mac	
On-Screen Display (OSD)		Yes	
Push Button Control		8, Available When Connected to a KVM Drawer	
Hotkey Control		Yes	
Auto-Scan Interval		3, 8, 15, 30 Seconds	
Programmable Scan Pattern		Yes	
Plug-and-Play		Yes	
Rack-Mounted		Yes, 19" Industry Standard	
Cable Length (Max)		30M (100ft) at CONSOLE 30M (100ft) at PC ports for PS/2 5M at PC ports for USB	
Video Resolution		1920 x 1440, DDC2B	
LCD KVM Drawer Connector		C-36	
Computer Connectors	Keyboard + Mouse + Monitor (2-in-1) USB Interface	HDB15 x 8 Female (Grey)	HDB15 x 16 Female (Grey)
Console Connectors	Keyboard	PS/2 x 1	
	Mouse	PS/2 x 1	
	Monitor	HDB15 (Female) x 1	
Rear-Mount Brackets		1U-Height, Included	
Height		1U	
Power Consumption (Max.)		12V DC, 3A (When Connected to a TFT LCD Drawer) 9 ~12V DC, 500mA (Not Connected to a TFT LCD Drawer)	
Dimensions H x W x D (mm)		44 x 404 x 114	

Features

- Manage multiple computers from two locations
- Cascade configuration expands system capability
- Auto-scan automatically selects computers sequentially
- Assigns individual computers with unique and meaningful names.
- Identifies and selects computers by the names
- Programmable scan filters unused computers
- Stores system settings and name entries to non-volatile memory
- Password security locks computer from unauthorized access
- Gains complete control with easy-to-use OSD interface
- Hotkey functions allow easy computer access
- Keyboard states automatically saved and restored when switching computers
- Operating system independent, transparent to all applications
- Plug-n-play system configuration
- DDC2B compatible
- Supports optional multimedia module for microphones and stereo speakers
- Cascadable to all 19" rack mountable PS/2 KVM Switches
- Special 3-in-1 cables save spaces and offer the most flexibility
- 16-port model is only 1U in height
- Supports computers with either PS/2 or USB interface
- Supports Sun servers, HP servers and Mac

Connection Pattern



1-to-2 cable for USB PC connection




1-to-3 cable for PS/2 PC connection



PS/2 PC



USB PC



Mac